

# Spredway<sub>®</sub> Grain Spreaders

Features you want in a size you need!

- The most reliable grain spreader you can buy.
- Pre-spread disc and inner ring help provide even spreading. The optional pre-spread funnel further enhances even spreading.
- Totally-enclosed, continuous-duty motors mounted outside spreader cone for optimum performance.
- Standard Spredway®: 3000 bph, 1/2 hp motor, fits up to 33' diameter bins.
- High-Capacity Spredway®: 3000 - 5000 bph, 3/4 hp motor, fits up to 48' bins.
- Super High-Capacity Spredway®: 5000 - 7000 bph, 1 1/2 hp motor, fits up to 60' diameter bins.



## Gravity Spreader - For Motor Free Spreading

- Up to10,000 Bu/Hr.
- Two sizes:
  - 21' 30' diameters
  - 30' 105' diameters
- No motors or cords.
- Unit rotates in response to grain flow, providing uniform distribution of grain.



## The Best-Selling Grain Spreader - Spredway®

Outstanding features have made the reliable Sukup Spredway® #1

#### **Easily Adjustable Pan**

 The angle of the Spredway® spreader pan can be easily adjusted from the top to control the grain distribution pattern.

The handle is easily accessible, unlike other spreaders which must be adjusted from below the unit.

 Adjusting the pan matches the grain spread distance to different bin diameters.

 A Split Spreader Pan (standard) divides the grain discharge resulting in a more evenly balanced flow, which makes the spreader operate more smoothly.

> PATENT -NO.-8.123.452

Tools available for easy adjustment.



- There are no motors or gear boxes inside the spreader funnel to hamper grain flow.
- Mounting the motor outside of the spreader cone prevents warm grain from overheating the motor.

#### Totally Enclosed, High Horsepower Motor

All Sukup Spredways are equipped with heavy-duty,
high-horsepower motors to ensure optimum performance.
Horsepower ratings for the different models are listed in
the chart below.

#### **Dependable**

- The simple design of the Spredway® includes a machined pulley to ensure that the drive belt remains in position under the heaviest grain flow conditions.
- No gearbox and a minimum of moving parts make Spredway® the most dependable grain spreader you can buy.
- Permanently-lubricated bearings eliminate climbing the bin to grease bearings or oil gears.



The pre-spread disc and ring, standard on all Spredways, combine to create a uniform flow of grain to the spread pan for even spreading.

### **Exclusive Pre-Spread Funnel**

Most problems with uneven spreading occur when grain does not fall into the center of the grain spreader. The Sukup Pre-Spread Funnel is an optional accessory that directs grain to the center of the Spredway's pre-spread disc, creating even and uniform spreading action.



#### **Rigid Mounting Brackets**

- Special, two-piece design allows for vertical and horizontal adjustment to level the spreader.
- The rigid mount prevents spreader movement.
- Additional hanger brackets are available for mounting in bins that are not compatible with the rigid brackets.



## Spredway® Specifications

-production of the contraction							
Model	Capacity - bu/hr	Motor Size	Pre-Spread disc dia.	Spreader Pan Style	Motor Pulley Dia.	Cone	Bin Dia.
Standard	up to 3000	1/2 hp	3 1/2"	Split	1 3/4"	19" x 12"	18' - 33'
High-Capacity	3000 - 5000	3/4 hp	3 1/2"	Split	2 1/4"	19" x 12"	24' - 48'
Super High-Capacity	5000 - 7000	1 1/2 hp	8"	Split	2 1/4"	19" x 13"	36' - 60'



Sukup Manufacturing Co. ■ www.sukup.com

Box 677 ■ 1555 255th St. ■ Sheffield, IA 50475-0677 ■ ph 641.892.4222 ■ fx 641.892.4629 ■ info@sukup.com

**Distribution Centers** 

Arcola, IL 61910 980 E. State Rte. 133 ph 217.268.3026 illinois@sukup.com Aurora, NE 68818 1705 Hwy, 34 E. ph 402.694.5922 nebraska@sukup.com Cameron, MO 64429 7426 NE 352nd St. ph 816.649.2226 missouri@sukup.com **Defiance, OH 43512** 7724 Rte. 66 N. ph 419.784.9871 ohio@sukup.com

Jonesboro, AR 72403 5917 E. Johnson Ave. ph 870.932.7547 arkansas@sukup.com Watertown, SD 57201 2701 Piper Ave. ph 605.882.6697 southdakota@sukup.com